

Stationäre Pulverumfüllmaschinen No. 153 000 · RAPID-N

The RAPID-N filling unit accomplishes the requirements of the EN3-norm by speed, precision, economy and cleanness. The RAPID-N fills extinguishers from 1 - 12 kg and larger cylinders by means of special filling adaptor.

The filling takes place by suction out of a silo, BIG-BAG or powder storage container (option – not included) directly into the fire extinguisher without any additional labour.

The filling is absolutely dust-free out of this powder storage directly into the extinguisher.

The precise filling is effected by a digital scale. The requested weight is sored at the scale and after reaching the filling quantity the scale stops automatically.

The height adjustment for different types of extinguisher result manual by pneumatic cylinder.

The RAPID-N can be used by manufacturers of extinguishers, airportfire brigades, operating fire brigades and service offices.



TECHNISCHE DATEN

Dimensions (I x w x h): Motor-capacity: Pump-capacity: Drive: Compressed-air: Control: Construction: Colour: approx. 1100 x 1000 x 2300 mm 2.2 kW 25 kg/min (according to powder quality) three-phase current 230/400 V, 16 A, 50 Hz + N + PE 6 – 10 bar SPS / Digital scale, precision +/- 10 g steel / aluminium hammer finish painted blue The RAPID-N is convincing by its technology and shows the possibility within the filling of powder fire extinguisher.