

CO<sub>2</sub>-Filling Units

No. 253 000 · KU4 · KUD4 · KUS4

CO<sub>2</sub>-Filling Unit KU4 (230V), KUD4 (compressed air driven) and KUS4 (380 V) for filling CO<sub>2</sub> Cylinder from 150 g up to 45 kg.



**Unit consists of:**

- » Steel case with ergonomic user interface
- » CO<sub>2</sub> pump
- » Safety valve 130 bar
- » Electric cable, 5 m, oil and acid resistant
- » electric control panel with indicator light
- » 2 pieces of CO<sub>2</sub> hoses

**Optional extra charge:**

- » CO<sub>2</sub> input filter

**TECHNICAL DATA**

**KU4 (No. 253 000)**

Capacity:	max. 4,5 kg/min
Motor:	AC 230 V, 50 Hz
Weight:	approx. 59 kg
Dimensions (l x w x h):	approx. 500 x 700 x 1000 mm
Colour:	hammer finish painted blue

**TECHNICAL DATA**

**KUD4 (No. 205 000)**

Capacity:	max. 4,5 kg/min
Motor:	compressed-air-driven 8 – 10 bar
Weight:	approx. 45 kg
Dimensions (l x w x h):	approx. 500 x 700 x 1000 mm
Colour:	hammer finish painted blue

**TECHNICAL DATA**

**KUS4 (No. 233 000)**

Capacity:	max. 4,5 kg/min
Motor:	three-phase current 230/400 V, 50 Hz
Weight:	approx. 65 kg
Dimensions (l x w x h):	approx. 500 x 700 x 1000 mm
Colour:	hammer finish painted blue