





CO₂-Filling Units

No. 256 000 · KU6-DI

CO₂-filling unit KU6 suitable to fill any size, shape or make of CO₂-cartridges (from 20 g) and CO₂-bottles (up to 6 kg) with the universal filling head. CO₂-unit with integrated digital scale 30 kg in table form with 40 mm thick wooden board.



CO₂-Filling Units

No. 256 000 · KU6-DI · KUD6-DI · KUS6-DI

The unit is equipped with:

- » Silent directly flanged CO₂-pump
- » Filling speed control for slow filling of cartridges and fast filling of large bottles
- » Fine regulation for small cartridges
- » Fast filling for large cylinders
- » Digital scale (30 kg weighing range) with automatic cutoff feature – resolution 5 g or 10 g optional
- » Operation by electrovalves
- » Filling of large bottles more than 6 kg has to be carried out on a separate floor scale with automatic cut-off feature (scale not included)
- » No pre-cooling system for CO₂ source bottle required
- » Emptying of CO₂ master bottle up to 95%

Optional available at extra charge:

- » Equipped with mechanical sliding weight scale
- » Electric supply with 230/400 V, 60 Hz
- » Equipped with label printer
- » CO₂-steel filter



TECHNICAL DATA KU6-DI (No. 256 000)

Capacity:	max. 5 kg/min
Operating pressure:	max. 130 bar
Safety valve:	130 bar
Motor:	AC 230 V, 50 Hz
Dimensions (l x w x h):	approx. 1000 x 750 x 850 mm
Colour:	hammer finish painted blue
Standard accessories:	<ul style="list-style-type: none"> » 3 adaptors for filling of CO₂-cartridges, Ø 18, 25 and 32 mm » 1 CO₂ high-pressure hose, 2 m » 1 rotary filling valve "DF 1" to fill CO₂-bottles » 1 height adjustable support, KS-6 » 1 set of sealings for filling adaptors

TECHNICAL DATA KUD6-DI (No. 209 000)

Capacity:	max. 5 kg/min
Operating pressure:	max. 130 bar
Safety valve:	130 bar
Motor:	AC 230 V, 50 Hz
Air pressure:	8-10 bar 800 l/Air/min
Dimensions (l x w x h):	ca. 1000 x 750 x 850 mm
Colour:	hammer finish painted blue or silvergrey
Standard accessories:	<ul style="list-style-type: none"> » 3 adaptors for filling of CO₂-cartridges, Ø 18, 25 and 32 mm » 1 CO₂ high-pressure hose, 2 m » 1 rotary filling valve "DF 1" to fill CO₂-bottles » 1 height adjustable support, KS-6 ; 1 set of sealings for filling adaptors

TECHNICAL DATA KUS6-DI (No. 237 000)

Capacity:	max. 5 kg/min
Operating pressure:	max. 130 bar
Safety valve:	130 bar
Motor:	three-phase current 230/400 V, 50 Hz
Dimensions (l x w x h):	ca. 1000 x 750 x 850 mm
Colour:	hammer finish painted blue
Standard accessories:	<ul style="list-style-type: none"> » 3 adaptors for filling of CO₂-cartridges, Ø 18, 25 and 32 mm » 1 CO₂ high-pressure hose, 2 m » 1 rotary filling valve "DF 1" to fill CO₂-bottles » 1 height adjustable support, KS-6 » 1 set of sealings for filling adaptors