

CO₂-Filling Units

No. 263 000 · KUD6-DI-N₂ PROTECT

Combined filling unit for Carbon Dioxide (CO₂) and Nitrogen (N₂) for small cartridges fire extinguishers and cylinders of all makes and sizes with the FRITZ EMDE universal filling rail.



The unit is equipped with:

- » digital scale (resolution 5 g) with automatic cut-off
- » Compressed-air driven CO₂-pump
- » Compressed-air driven N₂-pump
- » Filling speed regulator
- » Electrically relief valve
- » Universal FRITZ EMDE filling rail
- » CO₂-filter
- » Safety valve (130 bar)

Standard accessory:

- » 3 adaptors for CO₂-cartridges: 18 mm, 25 mm und 32 mm
- » 1 CO₂-High-Pressure hose 2 m
- » 1 DF1-adaptor for filling of CO₂-cylinders
- » 1 KS 5 support
- » 1 set of socket wrenches, 10 – 32 mm
- » 1 CO₂-steel filter

KUD6-DI-N₂ (No. 261 000)



TECHNICAL DATA

Filling capacity CO ₂ :	max. 5 kg/min
Working pressure:	max. 130 bar
Safety valve:	130 bar
Motor:	AC 230 V, 50 Hz, 10 A
Dimension (l x w x h):	approx. 1300 x 750 x 1250 mm
Working height:	850 mm
Colour:	hammer finish painted blue

Accessories available at extra charge:

- » Floor scale with automatic cut-off 200 kg, 20 g resolution, display integrated in filling unit scale platform approx. 600 x 400 mm incl. cylinder bracket
- » CO₂-QUICK fast filling adaptor
- » Raisable safety guard for filling rail
- » Label printer